

Acceptable ASTM A563 Nut, Grade, Finish and Style And ASTM F436 Washer Type and Finish for Threaded Anchor Rods

Anchor Rod	Anchor Rod Size mm (in.)*	Finish	ASTM A563 Nut Style, Grade and Finish	ASTM F436 Washer Type and Finish^b
F1554 Grade 36	6-38 (1/4 - 1 1/2)	Plain (uncoated)	Hex: A, B, D, DH; plain Heavy Hex: A, B, D ^C , C3, D ^C , DH ^d , DH3; plain	1; plain
		Galvanized	Hex: A, B, D ^C , DH ^d ; Galvanized and lubricated Heavy Hex: A, B, C ^C , C3, D ^C , DH ^d , DH3; galvanized and Lubricated	1; galvanized
	Over 38-100 (1 1/2 - 4)	Plain (uncoated)	Heavy Hex: A, B, C ^C , C3, D ^C , DH ^d , DH3; plain	1; plain
		Galvanized	Heavy Hex: A, B, C ^C , C3, D ^C , DH ^d , DH3; galvanized and Lubricated	1; galvanized
F1554 Grade 55	6-38 (1/4 - 1 1/2)	Plain (uncoated)	Hex: A, B, D ^C , DH ^d ; plain Heavy Hex: A, B, C ^C , C3, D ^C , DH ^d , DH3; plain	1; plain
		Galvanized	Heavy Hex: A, B, C ^C , C3, D ^C , DH ^d , DH3; galvanized and Lubricated	1; galvanized
A706 Grade 60	Over 38-100 (1 1/2 - 4)	Plain (uncoated)	Heavy Hex: A, B, C ^C , C3, D ^C , DH ^d , DH3; plain	1; plain
		Galvanized	Heavy Hex: A, B, C ^C , C3, D ^C , DH ^d , DH3; galvanized and Lubricated	1; galvanized
F1554 Grade 105	6-38 (1/4 - 1 1/2)	Plain (uncoated)	Hex: D ^C , DH ^d ; plain Heavy Hex: C ^C , C3, D ^C , DH ^d , DH3; plain	1; plain
		Galvanized	Heavy Hex: DH ^d , DH3; galvanized and lubricated	1; galvanized
	Over 38-100 1 1/2 - 4	Plain (uncoated)	Heavy Hex: DH ^d , DH3; plain	1; plain
		Galvanized	Heavy Hex: DH ^d , DH3; galvanized and lubricated	1; galvanized